

TW80

Takeuchi®

The Power of Product and Support



All Takeuchi wheel loaders share our commitment to the highest standards in quality and performance. They are engineered to be durable and powerful while providing mobility and stability. The specifications and features make the TW80 reliable to own, comfortable to operate and a performance leader on the job.

When you invest in a Takeuchi, you receive over five decades of equipment innovation, the quality assurance of ISO-9001 certification and responsive after sales support from an industry leader.

Try a Takeuchi and feel the power.

TW80 Wheel Loader

TW80 Wheel Loader

- Spacious and comfortable operator's compartment allows for productive and fatigue-free operation
- Hydrostatic drive system with outboard planetary final drives provides durable and efficient power transfer
- Momentary pushbutton control of 100% front and rear axle differential lock provides additional traction in harsh terrain
- Frame oscillation and articulation enhances mobility, stability and operator comfort
- Forward, neutral and reverse functions controlled on-the-go with electrohydraulic thumb switches

DIMENSIONS AND WEIGHT

Operating Weight (lbs).....	12,677
Overall Width Without Bucket.....	80.7"
Width With Flotation Tires.....	81.5"
Overall Height (Cab).....	105.7"
Height With Flotation Tires.....	106.7"
Overall Length With Bucket.....	219.7"
Maximum Lift Height to Bucket Pin.....	133.1"
Dump Height Fully Raised.....	102.6"
Max. Dump Angle Fully Raised.....	45°
Max. Bucket Rollback at Ground Level.....	48°
Reach Fully Raised.....	29.1"

PERFORMANCE

Tipping Load, Straight (lbs).....	9,420
Tipping Load, Full Turn (lbs).....	8,294
Operating Capacity (lbs)	
50% of Full Turn Tipping Load.....	4,147
Breakout Force (lbs) Bucket Cylinders.....	15,287
Lift Capacity at Ground Level (lbs).....	13,567
WITH PALLET FORKS	
Static Tipping Load,	
Straight and Articulated (lbs).....	6,839
Lifting Capacity (lbs/ft).....	10,813
Payload 80% Even Surface (lbs).....	5,470
Payload 60% Uneven Surface (lbs).....	4,103
CYCLE TIME	
Raise-Full Load (seconds).....	6.0
Lower-No load (seconds).....	4.1
Dump-Full Load (seconds).....	1.2

HYDRAULIC SYSTEM

Hydraulic Reservoir Capacity (gal).....	19.8
Auxiliary Hydraulic Flow (gpm).....	19.8
System Operating Pressure (psi).....	3,263

ENGINE

Make/Model.....	Deutz BF4L 2011
Horsepower/RPM (SAE gross).....	73 / 2,300
Maximum Torque (ft-lb/rpm).....	170 / 1,600
Cylinders/CID.....	4 / 189.8
Engine Lubrication (qt).....	11.6
Fuel Tank Capacity (gal).....	26.4
Fuel Consumption (65% of full load) gal/hr.....	2.62
Electrical System (volt/amp).....	12 / 80

UNDERCARRIAGE

Transmission Type.....	Hydrostatic
Axle Type.....	Planetary Rigid Axles
Parking/Service Brake Type	
...Spring Applied Hydraulically Released Wet Disc	
Tires Heavy Duty Flotation	
.....15-19.5 12-ply.....	400/70-20 8-ply
Tread Width.....	64.6"
Wheelbase.....	85.8"
Articulation.....	40° / 40°
Oscillation.....	+ or - 12°
Travel Speed (mph).....	12.4
Ground Clearance.....	18.8"

OPTIONAL

Buckets	
Width.....	81.5"
Capacity SAE Heaped (cu yd).....	1.3
Air Conditioning Kit	

STANDARD FEATURES

- Low and high range travel speed
- Sound absorbing ROPS/FOPS cab with heat
- Operator's compartment entry and exit grab handles and steps
- Dual element air cleaner with restriction indicator
- Front and rear work lights
- Automatic fuel bleed system
- Hydraulic quick attach
- Bucket float function
- Six-way adjustable suspension seat with retractable seat belt
- Two cab mounted rear view mirrors
- Back-up alarm
- Horn
- Vandalism protected lockable engine compartment
- Lift arm safety stop
- Adjustable arm rests
- Auxiliary hydraulic lines conveniently plumbed to bottom of loader arms
- 100% hydraulic inching pedal
- Sun visor, ceiling lamp, coat hook and storage compartment
- Windshield and rear window wiper and wash unit
- Adjustable steering column
- Rear window defrost
- Rear tires follow the same track as front tires
- Z-pattern lift kinematics
- Automatic bucket positioning