

# TB290

## Product Comparison

	Takeuchi TB290	Bobcat E85	Case CX80C	Caterpillar 308E2 CR SB	John Deere 85G	Komatsu PC88MR-10	Kubota KX080-4S	Volvo ECR88D	Yanmar ViO80-1A
<b>PERFORMANCE</b>									
Tail Swing Design	Conventional	Minimal	Conventional	Minimal	Minimal	Minimal	Conventional	Zero	Zero
Operating Weight	18,630 lb (8,450 kg)	18,977 lb (8,608 kg)	18,938 lb (8,590 kg)	18,519 lb (8,500 kg)	19,182 lb (8,701 kg)	18,739 lb (8,500 kg)	18,365 lb (8,330 kg)	19,600 lb (8,890 kg)	18,136 lb (8,226 kg)
Max Digging Depth	15' 0" (4,580 mm)	15' 6" (4,724 mm)	15' 4" (4,674 mm)	15' 5" (4,699 mm)	14' 10" (4,521 mm)	15' 0" (4,565 mm)	15' 1" (4,600 mm)	14' 10" (4,530 mm)	15' 4" (4,674 mm)
Max Dump Height	17' 3" (5,260 mm)	16' 5" (5,029 mm)	15' 11" (4,851 mm)	16' 5" (5,003 mm)	16' 8" (5,080 mm)	15' 8" (4,770 mm)	17' 3" (5,250 mm)	17' 2" (5,220 mm)	15' 2" (4,623 mm)
Max Reach	24' 5" (7,435 mm)	23' 7.2" (7,193 mm)	24' 10" (7,569 mm)	24' 1" (7,341 mm)	25' 3" (7,700 mm)	24' 1" (7,345 mm)	24' 0" (7,330 mm)	24' 1" (7,350 mm)	23' 5" (7,137 mm)
Max Bucket Digging Force	16,565 lb (7,514 kg)	16,269 lb (7,379 kg)	12,792 lb (5,802 kg)	13,534 lb (6,139 kg)	10,476 lb (4,752 kg)	13,781 lb (6,250 kg)	14,660 lb (6,650 kg)	12,770 lb (5,792 kg)	14,275 lb (6,475 kg)
Max Arm Digging Force	8,161 lb (3,702 kg)	8,253 lb (3,743 kg)	7,600 lb (3,447 kg)	7,891 lb (3,579 kg)	6,902 lb (3,131 kg)	8,161 lb (3,702 kg)	8,554 lb (3,880 kg)	7,730 lb (3,506 kg)	8,363 lb (3,793 kg)
Traction Force	19,780 lb (8,972 kg)	NP	13,300 lb (6,032 kg)	14,500 lb (6,577 kg)	14,661 lb (6,650 kg)	15,040 lb (6,822 kg)	14,878 lb (6,749 kg)	14,613 lb (6,628 kg)	NP
<b>ENGINE</b>									
Make / Model	Yanmar / 4TNV98CT	Yanmar/4TNV98C	Isuzu / AP-4LE2X	Cat / C3.3B	Yanmar / 4TN-V98C-WHBW	Kom / SAA4D95LE-6	Kubota / V3307 CR TE4	Volvo / D2.6H	Yanmar / 4TNV98
Tier Rating	EPA Final Tier 4	EPA Final Tier 4	EPA Final Tier 4	EPA Final Tier 4	EPA Final Tier 4	EPA Final Tier 4	EPA Final Tier 4	EPA Final Tier 4	EPA Interim Tier 4
Horsepower	69.2 hp (51.6 kW)	65.9 hp (49.1 kW)	54 hp (40.3 kW)	66.6 hp (49.7 kW)	56.9 hp (42.4 kW)	67.9 hp (50.6 kW)	66.6 hp (49.7 kW)	58.0 hp (43.3 kW)	54.6 hp (40.7 kW)
Rated Engine Speed	2,000 rpm	2,100 rpm	2,000 rpm	2,400 rpm	2,000 rpm	1,950 rpm	2,000 rpm	2,000 rpm	2,000 rpm
Max Torque	227.2 ft-lb (308 Nm)	NP	142.0 ft-lb (193 Nm)	NP	NP	NP	NP	162.0 ft-lb (219.6 Nm)	NP
<b>UNDERCARRIAGE</b>									
Track Width	17.7" (450 mm)	17.7" (450 mm)	18" (457 mm)	17.7" (450 mm)	18" (457 mm)	18" (457 mm)	17.7" (450 mm)	18" (457 mm)	17.7" (450 mm)
Ground Pressure	5.5 psi (37.9 kPa)	5.5 psi (38.1 kPa)	5.5 psi (38.0 kPa)	5.3 psi (36.3 kPa)	6.0 psi (41.4 kPa)	5.4 psi (37.3 kPa)	5.2 psi (35.8 kPa)	5.8 psi (40.0 kPa)	5.2 psi (35.8 kPa)
Travel Speed Low Range	1.6 mph (2.6 km/h)	1.7 mph (2.7 km/h)	2.1 mph (3.3 km/h)	1.7 mph (2.8 km/h)	1.9 mph (3.1 km/h)	1.9 mph (3.0 km/h)	1.7 mph (2.7 km/h)	1.6 mph (2.6 km/h)	1.6 mph (2.5 km/h)
Travel Speed High Range	3.1 mph (5.0 km/h)	2.9 mph (4.7 km/h)	3.2 mph (5.1 km/h)	3.2 mph (5.1 km/h)	3.1 mph (5.0 km/h)	3.1 mph (5.0 km/h)	3.0 mph (5.0 km/h)	3.0 mph (4.8 km/h)	2.8 mph (4.5 km/h)
<b>HYDRAULIC SYSTEM</b>									
Total Hydraulic Flow	62.5 gpm (236.6 L/m)	NP	43.8 gpm (165.8 L/m)	39.6 gpm (170.0 L/m)	53.0 gpm (200 L/m)	60.7 gpm (229.8 L/m)	44.6 gpm (168.8 L/m)	4833 gpm (183 L/m)	56.3 gpm (213 L/m)
Auxiliary Hydraulic Flow	26.4 / 14.5 gpm (100.0 L/m / 55.0 L/m)	25.1 gpm (95.0 L/m)	NP	33.8 / 16.9 gpm (128 L/m / 70.0 L/m)	NP	33 gpm (125 L/m)	26.4 / 17.6 gpm (100 L/m / 66.6 L/m)	24.0 / 9.0 gpm (90 L/m / 34 L/m)	31.7 gpm (120.0 L/m)
Hydraulic System Pressure	3,990 psi (27.5 MPa)	3,045 psi (21.0 MPa)	4,260 psi (29.4 MPa)	4,061 psi (27.9 MPa)	3,771 psi (26.0 MPa)	3,844 psi (26.5 MPa)	NP	4,264 psi (29.4 MPa)	3,481 psi (24.0 MPa)
Hydraulic Reservoir Capacity	19.3 gal (73.0 L)	NP	13.5 gal 51.1 L	21.7 gal (82.0 L)	15.0 gal (56.0 L)	14.8 gal (56.0 L)	19.8 gal (75.0 L)	22.0 gal (84.0 L)	NP
<b>DIMENSIONS</b>									
Width	7' 3" (2,210 mm)	7' 3" (2,210 mm)	7' 7" (2,311 mm)	7' 7" (2,311 mm)	7' 7" (2,311 mm)	7' 8" (2,330 mm)	7' 3" (2,200 mm)	7' 7" (2,311 mm)	7' 5" (2,261 mm)
Height	8' 5" (2,565 mm)	8' 3.8" (2,535 mm)	9' 1" (2,769 mm)	8' 4" (2,550 mm)	9' 6" (2,896 mm)	9' 1" (2,760 mm)	8' 4" (2,540 mm)	8' 11" (2,718 mm)	8' 10" (2,692 mm)
Length (Transport)	21' 10" (6,660 mm)	20' 6" (6,248 mm)	22' 1" (6,731 mm)	20' 10" (6,340 mm)	22' 5" (6,820 mm)	21' 1" (6,426 mm)	21' 2" (6,452 mm)	21' 1" (6,426 mm)	21' 2" (6,452 mm)
Ground Clearance	15.0" (385 mm)	NP	14.0" (356 mm)	NP	14.0" (360 mm)	16.0" (406 mm)	14.0" (356 mm)	16.0" (406 mm)	15.0" (381 mm)
Boom Swing (Degrees L / R)	70 / 60	64 / 61	NP	60 / 50	60 / 60	NP	70 / 60	60 / 70	57 / 60
Front Swing Radius	8' 2" (2,495 mm)	NP	9' 11" (3,023 mm)	9' 2" (2,794 mm)	9' 6" (2,890 mm)	9' 6" (2,900 mm)	8' 2" (2,489 mm)	8' 8" (2,642 mm)	8' 11" (2,718 mm)
Tail Swing Radius	5' 5" (1,650 mm)	NP	5' 6" (1,676 mm)	4' 9" (1,448 mm)	4' 11" (1,499 mm)	4' 10" (1,485 mm)	4' 9.5" (1,461 mm)	4' 3" (1,295 mm)	3' 9" (1,143 mm)