

TB370

TAKEUCHI

Machine Features

ENGINE

- EPA Tier 4 Final / EU Stage V
- Turbocharged
- DOC+DPF Exhaust After Treatment
- Automatic Fuel Priming System
- Dual Element Air Cleaner
- Working Modes; Standard and ECO
- Automatic Cold Start Device
- High Capacity Radiator and Hydraulic Oil Cooler
- Engine Safe Start System
- 90 Amp Alternator

UNDERCARRIAGE AND FRAME

- Triple Flange Track Rollers
- 2-Speed Axial Piston Travel Motors with Counterbalance Valves
- Integrated Load Sensing Automatic Shift Down
- Integrated Fail-Safe Mechanical Parking Brake
- Automatic Slew Brake with Shock-less Relief Valve
- Concealed in Frame Travel Motor Hoses
- High Torque Final Planetary Drives
- Heavy Duty Backfill Blade with Float
- Large Wrap-Around Counterweight
- Power Angle Blade (Optional)
- 15.7" Rubber Crawlers
- 15.7" Steel Crawlers (Optional)
- 15.7" Segmented Rubber Crawlers (Optional)

OPERATOR'S STATION

- Cab with Automatic Climate Control System
- Windshield Wiper and Washer
- Skylight with Sunshade
- DAB Radio with Bluetooth
- 8" Color Multifunction LCD Touchscreen Display
- Jog Dial with Multifunction Panel
- Multifunction Joystick Controls
- Hand Dial Electronic Throttle Control
- Rear View Camera
- Pilot Control Safety Lockout System
- ROPS/FOPS/OPG Level 1 Cab
- Deluxe High Back Suspension Seat
- Removable Washable Floor Mat
- Cup Holder
- Adjustable Arm Rests
- 12 Volt Power Socket
- 2' Retractable Seat Belt
- 3" Retractable Seat Belt (Optional)

TAKEUCHI FLEET MANAGEMENT

- 2 Year Standard Service
- Minimize Downtime
- Remote Diagnostics
- Utilization Tracking
- Proactive Maintenance
- Control Costs
- Geofencing

HYDRAULIC & WORKING EQUIPMENT

- Variable Displacement, Axial Piston Hydraulic Pump with Tandem Gear Pumps
- Closed Center, Load Sensing Hydraulic System
- Cushioned Boom and Swing Cylinders
- Boom Holding Valve with Integrated Lift Overload Alarm
- Hydraulic Pilot Controls
- High Flow Primary Auxiliary Circuit Plumbed to Mid-Arm with Shutoff Valves
- Secondary Auxiliary Hydraulic Circuit Plumbed to Mid-Arm with Shutoff Valves
- Integrated Hydraulic Attachment Quick Connect System (Coupler Optional)
- Automatic One-Way Flow Valve for Primary Auxiliary Circuit
- Automatic Auxiliary Circuit Pressure Release Feature
- Pilot Pressure Accumulator Valve
- Pilot Control Pattern Change Valve (ISO/SAE)
- LED Work Lights
- Travel Alarm
- Main Boom Cylinder Guard
- Long Arm with Integrated Thumb Mount
- Dual Pin Position Bucket (Optional)
- Hydraulic Pin Grabber Coupler (Optional)
- Mechanical Bucket Quick Coupler (Optional)
- Main Pin Hydraulic Thumb (Optional)