

	Takeuchi TB370	Bobcat E63	Caterpillar 306 CR	John Deere 60G
<b>PERFORMANCE</b>				
Tail Swing Design	Conventional	Conventional	Minimal	Minimal
Operating Weight	14,850 lb (6,735 kg)	13,779 lb (6,250 kg)	14,877 lb (6,748 kg)	13,690 lb (6,210 kg)
Max Digging Depth	13' 4.7" (4,085 mm)	13' 6" (4,115 mm)	13' 6" (4,115 mm)	13' 6" (4,120 mm)
Max Dump Height	14' 11" (4,545 mm)	14' 0" (4,267 mm)	15' 1" (4,597 mm)	14' 6" (4,410 mm)
Max Reach	21' 11.4" (6,690 mm)	20' 4.8" (6,218 mm)	21' 11" (6,680 mm)	21' 6" (6,560 mm)
Max Bucket Digging Force	10,880 lb (4,935 kg)	9,731 lb (4,414 kg)	11,578 lb (5,252 kg)	9,240 lb (4,191 kg)
Max Arm Digging Force	6,610 lb (2,998 kg)	5,767 lb (2,616 kg)	5,957 lb (2,702 kg)	6,060 lb (2,749 kg)
Traction Force	16,480 lb (7,475 kg)	NP	12,589 lb (5,710 kg)	NP
<b>ENGINE</b>				
Make / Model	Kubota / V2607-CR-TE5B	Yanmar/4TNV98C	Caterpillar / C2.4	Yanmar / 4TNV98C-WHB
Tier Rating	EPA Final Tier 4	EPA Final Tier 4	EPA Final Tier 4	EPA Final Tier 4
Horsepower	56.8 hp (42.4 kW)	59.4 hp (44.3 kW)	57.9 hp (43.2 kW)	53.0 hp (39.6 kW)
Rated Engine Speed	2,200 rpm	2,100 rpm	2,200 rpm	2,000 rpm
Max Torque	157 ft-lb (213.4 Nm)	NP	NP	NP
<b>UNDERCARRIAGE</b>				
Track Width	15.7" (400 mm)	15.7" (400 mm)	16" (406 mm)	16" (406 mm)
Ground Pressure	5.4 psi (37.0 kPa)	5.1 psi (35.2 kPa)	5.7 psi (39.3 kPa)	5.2 psi (35.9 kPa)
Travel Speed Low Range	1.6 mph (2.5 km/h)	1.6 mph (2.5 km/h)	1.7 mph (2.7 km/h)	1.8 mph (2.9 km/h)
Travel Speed High Range	2.9 mph (4.7 km/h)	2.9 mph (4.7 km/h)	3.1 mph (5.0 km/h)	3.0 mph (4.8 km/h)
<b>HYDRAULIC SYSTEM</b>				
Total Hydraulic Flow	58.8 gpm (222.6 L/m)	NP	46 gpm (174.1 L/m)	38.0 gpm (144 L/m)
Auxiliary Hydraulic Flow	31.7 / 12.3 gpm (120 L/m / 46.6 L/m)	22.5 gpm (85.2 L/m)	24 gpm / 9 gpm (90.8 L/m / 34.1 L/m)	24.2 gpm (91.5 L/m)
Hydraulic System Pressure	3,550 psi (24.5 MPa)	3,046 psi (21.0 MPa)	3,553 psi (24.5 MPa)	NP
Hydraulic Reservoir Capacity	17.3 gal (65.5 L)	NP	10.3 gal (39 L)	21.1 gal (80 L)
<b>DIMENSIONS</b>				
Width	6' 10.7" (2,100 mm)	6' 6" (1,981 mm)	6' 6" (1,981 mm)	6' 7" (2,000 mm)
Height	8' 4" (2,540 mm)	8' 4" (2,550 mm)	8' 4" (2,540 mm)	8' 4" (2,540 mm)
Length (Transport)	19' 5.3" (5,925 mm)	18' 9.6" (5,730 mm)	19' 6" (5,944 mm)	19' 0" (5,790 mm)
Ground Clearance	13.2" (335 mm)	NP	12" (305 mm)	13.0" (335 mm)
Boom Swing (Degrees L / R)	79 / 51	70 / 50	NP	80 / 60
Front Swing Radius	8' 5.5" (2,580 mm)	NP	9' 9" (2,972 mm)	8' 4" (2,540 mm)
Tail Swing Radius	4' 9.4" (1,455 mm)	NP	4' 10" (1,473 mm)	4' 8" (1,410 mm)