

BROOMS

ATTACHMENT CATALOG



TAKEUCHI



BROOM ATTACHMENTS

- 82 | **PICK-UP BROOM**
- 83 | **ANGLE BROOM**

PICK-UP BROOM

TPUB72 / TPUB84



- + RECESSED & GUARDED MOTOR
- + HD BUCKET WITH WEAR BARS & BOLT-ON EDGE
- + OVERSIZED 2 in GREASABLE BEARING
- + PIN ADJUSTMENT SYSTEM TO QUICKLY SET BRISTLE HEIGHT
- + REPLACE WAFERS EASILY WITHOUT DISCONNECTING HOSES. STANDARD WITH POLY/WIRE WAFERS.

MODEL SPECS	TPUB72	TPUB84
Sweeping Width	72 in	84 in
Overall Width	79.8 in	91.8 in
Overall Height	31.3 in	
Overall Depth	62.4 in	
Number of 26" Diameter Wafers	35 in	41 in
Recommended Flow Rate	15-25 gpm Standard Flow Only	
Approximate Weight	1,120 lb	1,250 lb
Recommended Loader Capacity	Greater than 1,500 lb*	
*Recommended Loader Capacity w/ Water Kit Installed is 1,800 lb		



OPTIONS AND REPLACEMENT PARTS

OPTIONAL WATER KIT	TWK72LP	TWK84LP
Available for	TPUB72	TPUB84
Increased Depth	6 in	
Spray Width	31.3 in	
Number of Nozzles	5	6
Approximate Weight, Empty	111 lb	117 lb
Recommended Loader Capacity	Greater than 1,500 lb	
Number of Nozzles on spray bar. Use on Gutter Brush would add on nozzle.		

- + 30 GALLON TANK PROVIDES 20 MINUTES OF CONTINUOUS OPERATION
- + 12 VOLT, 2.1 GPM MAXIMUM PUMP WITH WIRING HARNESS
- + BOLT-ON ACCESSORY FOR PICK-UP BROOM ONLY. INCLUDES ALL REQUIRED COMPONENTS

OPTIONAL GUTTER BRUSH	TGB
Increased Sweeping Width, Straight	12 in
Increased Depth	28 in

- + INCREASES CLEANING WIDTH BY 12 in
- + ADJUSTABLE HYDRAULIC VALVE TO CONTROL BRUSH SPEED
- + CAN BE SECURED IN STORAGE POSITION WITHOUT REMOVAL

REPLACEMENT WAFER PACK	MODEL	QTY	WEIGHT
	TPWC72	35	82 lb
	TPWC84	41	96 lb

- + 8.125 in/26 in (I.D/O.D.) DIAMETER POLY/WIRE WAFERS
- + FOR TAKEUCHI PICK-UP BROOMS ONLY

REPLACEMENT EDGE KIT	MODEL	WEIGHT
	TUBEK72	82 lb
	TUBEK84	96 lb

- + 5/8 in x 6 in REVERSIBLE DOUBLE BEVEL STEEL EDGE
- + FOR TAKEUCHI PICK-UP BROOMS ONLY

ANGLE BROOM

TVAB72HA / TVAB84HA / TVAB96HA



- + SWING LINKAGE SYSTEM SELF-CENTERS BROOM WHEN ANGLED
- + RECESSED & GUARDED MOTOR
- + OVERSIZED 2 in GREASABLE BEARING
- + REPLACE WAFERS EASILY WITHOUT DISCONNECTING HOSES. STANDARD WITH POLY/WIRE WAFERS.
- + STANDS FLIP DOWN TO PROTECT BRISTLES DURING STORAGE

MODEL SPECS	TVAB72HA	TVAB84HA	TVAB96HA
Sweeping Width, Straight	72 in	84 in	96 in
Sweeping Width, Full Angle	64.2 in	74.8 in	85.5 in
Overall Width	81.1 in	93.1 in	105.1 in
Overall Width, Full Angle	83.9 in	94.3 in	105.4 in
Broom Angle	27°		
Overall Height / Depth, Straight	34 in / 74 in		
Number of 32" Diameter Wafers	35	41	47
Recommended Flow Rate	15-25 gpm Standard Flow Only		
Approximate Weight	1,035 lb	1,095 lb	1,160 lb
Recommended Loader Capacity	Greater than 1,500 lb		

OPTIONS AND REPLACEMENT PARTS

REPLACEMENT WAFER PACK	MODEL	QTY	WEIGHT
	TAWC72	35	144 lb
	TAWC84	41	168 lb
	TAWC96	47	192 lb

- + 10 in/32 in (I.D/O.D.) DIAMETER POLY/WIRE WAFERS
- + FOR TAKEUCHI ANGLE BROOMS ONLY

HYDRAULIC ANGLE

- + ONE CYLINDER DESIGN USING AN ELECTRIC CONTROL VALVE
- + 2 1/2 in BORE, 8 in STROKE CYLINDER WITH A NITROSTEEL ROD
- + GREASABLE 1 1/4 in CYLINDER AND 1 9/16 in LINKAGE PINS



CENTERING SWING LINKAGE


- + SWING LINKAGE SYSTEM WITH MULTIPLE PIVOT POINTS BETTER CENTERS BROOM IN FRONT OF THE LOADER WHEN ANGLED



519 BONNIE VALENTINE WAY | PENDERGRASS, GA 30567 | 706.693.3600

©2023 Takeuchi Manufacturing [U.S.], Ltd. All Rights Reserved. Printed in the U.S.A. In accordance with our established policy of continued improvement.
FORM: Takeuchi Brooms Attachment Catalog

PROPOSITION 65

 **WARNING:** This product can expose you to chemicals including Cadmium, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.